- 1. Shape of the hollow form
 - Start with a large opening
 - Make the HF with a easy taper
 - Try to do the whole form in one session, especially if it's green wood
 - Decision to make Seal or Not to seal
- 2. Drill your hole
 - Hand held drill bit
 - Forstner Bit with extension
- 3. Tools
 - 3 Main hollowing tools (Ellsworth set, make your own Cheaper)
 - Sharpen, Sharpen, Sharpen
 - Know how each tool cuts (Practice on bowl shape and watch the cut)

4. Relaxed Stance

- Hold tool with one hand resting on tool rest, lock in handle to your side
- Feet position so you can rock into the cut with out moving your hold on the tool
- Head should be looking over tool, not trying to see your cut

5. Starting the cut

- Speed is what you are comfortable with not always faster
- Keep tool rest about a inch away to make initial cuts
- Start by making a cone inside need to make room for shavings
- Leave lip a little thick to start
- Once tool is inside move tool rest close to opening

- Always keep tool center of form (Remember this when switching tools)
- Use your fingers on the tool to sense vibration
- Finesse not force!!!!!

CUT - CLEAN - MEASURE

- 6. Ron Brown Best Hollowing Rig
 - Easy set up
 - Comes with card for laser set up to measure
 - Get longer bars in the beginning
 - Laser is not the best Ron has good customer service Working on upgrading his laser
 - I ended up buying a laser at Staples for \$20 to replace the one with the rig

7. Measuring tools

- Digital Calipers
- Depth gauge
- Home made oval for measuring

Have FUN

- Call others for help
- Ask to come over to their shop
- Use the knowledge of the club, someone is in your area
- Chris cell # 586-610-3373